

Chem-Impex International Inc.

Tel: (630) 766-2112

E-mail: sales@chemimpex.com

Shipping and Correspondence:

935 Dillon Drive

Wood Dale, IL 60191 USA

Fax: (630) 766-2218

Web site: www.chemimpex.com

Manufacturing site:

825 Dillon Drive

Wood Dale, IL 60191 USA

S A F E T Y D A T A S H E E T

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	47084
NAME:	Nickel powder (1.0-1.5 micron)
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

SKIN SENSITIZATION (CATEGORY 1), H317

CARCINOGENICITY (CATEGORY 2), H351

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE, INHALATION
(CATEGORY 1), LUNGS, H372

SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 3), H402

LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 3), H412

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE
SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H317 MAY CAUSE AN ALLERGIC SKIN REACTION.
H351 SUSPECTED OF CAUSING CANCER
H372 CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE IF INHALED.
H412 HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

PRECAUTIONARY STATEMENT(S)

P201 OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.
P202 DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.
P260 DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/ SPRAY.
P264 WASH SKIN THOROUGHLY AFTER HANDLING.
P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.
P272 CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE.
P273 AVOID RELEASE TO THE ENVIRONMENT.
P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION.
P302 + P352 IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.
P308 + P313 IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ ATTENTION.
P333 + P313 IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ ATTENTION.
P363 WASH CONTAMINATED CLOTHING BEFORE REUSE.
P405 STORE LOCKED UP.
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS NONE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: Ni
MW: 58.69
CAS-NO. 7440-02-0

PURITY: $\geq 99.9\%$ (Trace metals basis)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
NICKEL POWDER (1.0-1.5 MICRON)		
	SKIN SENS. 1; CARC. 2; STOT RE 1; AQUATIC ACUTE 3; AQUATIC CHRONIC 3; H317, H351, H372, H402, H412	$\leq 100\%$

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	SHOW THIS MATERIAL SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.
IF INHALED	AFTER INHALATION: FRESH AIR. CALL IN PHYSICIAN.
IN CASE OF SKIN CONTACT	IN CASE OF SKIN CONTACT: TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/ SHOWER. CONSULT A PHYSICIAN.
IN CASE OF EYE CONTACT	AFTER EYE CONTACT: RINSE OUT WITH PLENTY OF WATER. CALL IN OPHTHALMOLOGIST. REMOVE CONTACT LENSES.
IF SWALLOWED	AFTER SWALLOWING: IMMEDIATELY MAKE VICTIM DRINK WATER (TWO GLASSES AT MOST). CONSULT A PHYSICIAN.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11.
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA	SUITABLE EXTINGUISHING MEDIA USE EXTINGUISHING MEASURES THAT ARE APPROPRIATE TO LOCAL CIRCUMSTANCES AND THE SURROUNDING ENVIRONMENT.
	UNSUITABLE EXTINGUISHING MEDIA FOR THIS SUBSTANCE/MIXTURE NO LIMITATIONS OF EXTINGUISHING AGENTS ARE GIVEN.
SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	NICKEL/NICKEL OXIDES NOT COMBUSTIBLE. AMBIENT FIRE MAY LIBERATE HAZARDOUS VAPOURS.
ADVICE FOR FIREFIGHTERS	STAY IN DANGER AREA ONLY WITH SELF-CONTAINED BREATHING APPARATUS. PREVENT SKIN CONTACT BY KEEPING A SAFE DISTANCE OR BY WEARING SUITABLE PROTECTIVE CLOTHING
FURTHER INFORMATION	SUPPRESS (KNOCK DOWN) GASES/VAPORS/MISTS WITH A WATER SPRAY JET. PREVENT FIRE EXTINGUISHING WATER FROM CONTAMINATING SURFACE WATER OR THE GROUND WATER SYSTEM.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	ADVICE FOR NON-EMERGENCY PERSONNEL: AVOID GENERATION AND INHALATION OF DUSTS IN ALL CIRCUMSTANCES. AVOID SUBSTANCE CONTACT. ENSURE ADEQUATE VENTILATION. EVACUATE THE DANGER AREA, OBSERVE EMERGENCY PROCEDURES, CONSULT AN EXPERT. FOR PERSONAL PROTECTION SEE SECTION 8.
ENVIRONMENTAL PRECAUTIONS	DO NOT LET PRODUCT ENTER DRAINS.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	COVER DRAINS. COLLECT, BIND, AND PUMP OFF SPILLS. OBSERVE POSSIBLE MATERIAL RESTRICTIONS (SEE SECTIONS 7 AND 10). TAKE UP DRY. DISPOSE OF PROPERLY. CLEAN UP AFFECTED AREA. AVOID GENERATION OF DUSTS.
REFERENCE TO OTHER SECTIONS	FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

**PRECAUTIONS FOR
SAFE HANDLING**

WORK UNDER HOOD. DO NOT INHALE
SUBSTANCE/MIXTURE.
IMMEDIATELY CHANGE CONTAMINATED CLOTHING.
APPLY PREVENTIVE SKIN PROTECTION. WASH HANDS
AND FACE AFTER WORKING WITH SUBSTANCE.
FOR PRECAUTIONS SEE SECTION 2.2.

**CONDITIONS FOR SAFE
STORAGE, INCLUDING
ANY
INCOMPATIBILITIES**

TIGHTLY CLOSED. KEEP AWAY FROM HEAT AND
SOURCES OF IGNITION. KEEP LOCKED UP OR IN AN
AREA ACCESSIBLE ONLY TO QUALIFIED OR
AUTHORIZED PERSONS.
KEEP IN A DRY PLACE. HANDLE AND STORE UNDER
INERT GAS.

STORAGE CLASS (TRGS 510): 4.1B: FLAMMABLE SOLID
HAZARDOUS MATERIALS

Store at RT

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2 NO
OTHER SPECIFIC USES ARE STIPULATED.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS**COMPONENTS WITH WORKPLACE CONTROL PARAMETERS**

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
NICKEL POWDER (1.0-1.5 MICRON)	7440-02-0	TWA	1.5 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
	REMARKS	NOT SUSPECTED AS A HUMAN CARCINOGEN		
		PEL	0.5 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS
		TWA	1 MG/M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS
		TWA	0.015 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		POTENTIAL OCCUPATIONAL CARCINOGEN		

BIOLOGICAL OCCUPATIONAL EXPOSURE LIMITS

COMPONENT	CAS-NO.	PARAMETERS	VALUE	BIOLOGICAL SPECIMEN	BASIS
NICKEL POWDER (1.0- 1.5 MICRON)	7440-02-0	NICKEL	5 MG/L	URINE	ACGIH - BIOLOGICAL EXPOSURE INDICES (BEI)
	REMARKS	END OF SHIFT AT END OF WORKWEEK			

		NICKEL	30 MG/L	URINE	ACGIH - BIOLOGICAL EXPOSURE INDICES (BEI)
		END OF SHIFT AT END OF WORKWEEK			

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS IMMEDIATELY CHANGE CONTAMINATED CLOTHING. APPLY PREVENTIVE SKIN PROTECTION. WASH HANDS AND FACE AFTER WORKING WITH SUBSTANCE.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU). SAFETY GLASSES

SKIN PROTECTION HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT
MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:DERMATRIL® (KCL 740, SIZE M)

SPLASH CONTACT
MATERIAL: NITRILE RUBBER
MINIMUM LAYER THICKNESS: 0.11 MM
BREAK THROUGH TIME: 480 MIN
MATERIAL TESTED:DERMATRIL® (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE EC APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION PROTECTIVE CLOTHING

**RESPIRATORY
PROTECTION**

REQUIRED WHEN DUSTS ARE GENERATED.
OUR RECOMMENDATIONS ON FILTERING RESPIRATORY
PROTECTION ARE BASED ON THE FOLLOWING
STANDARDS: DIN EN 143, DIN 14387 AND OTHER
ACCOMPANYING STANDARDS RELATING TO
THE USED RESPIRATORY PROTECTION SYSTEM.

**CONTROL OF
ENVIRONMENTAL
EXPOSURE**

DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	BLACK POWDER
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING	NO DATA AVAILABLE
POINT/FREEZING POINT	
BOILING POINT	NO DATA AVAILABLE
FLASH POINT	NO DATA AVAILABLE
EVAPOURATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	THE SUBSTANCE OR MIXTURE IS A FLAMMABLE SOLID WITH THE CATEGORY 2.
UPPER/LOWER	NO DATA AVAILABLE
FLAMMABILITY OR EXPLOSIVE LIMITS	
VAPOUR PRESSURE	1 HPA AT 1,810 °C
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	NO DATA AVAILABLE
WATER SOLUBILITY	INSOLUBLE
PARTITION	NOT APPLICABLE FOR INORGANIC SUBSTANCES
COEFFICIENT: N- OCTANOL/WATER	
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

OTHER SAFETY INFORMATION

NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	THE PRODUCT IS CHEMICALLY STABLE UNDER STANDARD AMBIENT CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	NO DATA AVAILABLE
INCOMPATIBLE MATERIALS	ACIDS, OXIDIZING AGENTS, SULFUR COMPOUNDS, HYDROGEN GAS, OXYGEN, METHANOL, ORGANIC SOLVENTS, ALUMINUM, FLUORINE, AMMONIA
HAZARDOUS DECOMPOSITION PRODUCTS	IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	LD50 ORAL - RAT - MALE AND FEMALE - > 9,000 MG/KG (OECD TEST GUIDELINE 401)
	INHALATION: NO DATA AVAILABLE
	DERMAL: NO DATA AVAILABLE
	NO DATA AVAILABLE
SKIN CORROSION/IRRITATION	SKIN - RABBIT RESULT: NO SKIN IRRITATION - 4 H (OECD TEST GUIDELINE 404)
SERIOUS EYE DAMAGE/EYE IRRITATION	EYES - RABBIT RESULT: NO EYE IRRITATION (OECD TEST GUIDELINE 405)
RESPIRATORY OR SKIN SENSITISATION	NO DATA AVAILABLE

**GERM CELL
MUTAGENICITY**

TEST TYPE: GENE MUTATION TEST
TEST SYSTEM: CHINESE HAMSTER FIBROBLASTS
METABOLIC ACTIVATION: WITHOUT METABOLIC
ACTIVATION
METHOD: OECD TEST GUIDELINE 476
RESULT: NEGATIVE
TEST TYPE: MICRONUCLEUS TEST
TEST SYSTEM: CHINESE HAMSTER FIBROBLASTS
METABOLIC ACTIVATION: WITH AND WITHOUT
METABOLIC ACTIVATION
METHOD: OECD TEST GUIDELINE 487
RESULT: NEGATIVE

CARCINOGENICITY
IARC:

SUSPECTED OF CAUSING CANCER.
2B - GROUP 2B: POSSIBLY CARCINOGENIC TO HUMANS
(NICKEL POWDER; [PARTICLE DIAMETER < 1 MM])

NTP:

1 - GROUP 1: CARCINOGENIC TO HUMANS (NICKEL
POWDER; [PARTICLE DIAMETER < 1 MM])
RAHC - REASONABLY ANTICIPATED TO BE A HUMAN
CARCINOGEN (NICKEL POWDER; [PARTICLE DIAMETER <
1 MM])

OSHA:

NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS
GREATER THAN OR EQUAL TO 0.1% IS ON OSHA'S LIST
OF REGULATED CARCINOGENS.

**REPRODUCTIVE
TOXICITY**

NO DATA AVAILABLE

**SPECIFIC TARGET
ORGAN TOXICITY -
SINGLE EXPOSURE**

NO DATA AVAILABLE

**SPECIFIC TARGET
ORGAN TOXICITY -
REPEATED EXPOSURE**

INHALATION - CAUSES DAMAGE TO ORGANS THROUGH
PROLONGED OR REPEATED EXPOSURE. - LUNGS

ASPIRATION HAZARD

NO DATA AVAILABLE

**ADDITIONAL
INFORMATION**

RTECS: NOT AVAILABLE

REPEATED DOSE TOXICITY - RAT - MALE AND FEMALE -
ORAL - 728 D - NOAEL (NO OBSERVED ADVERSE EFFECT
LEVEL) - 2.2 MG/KG - LOAEL (LOWEST OBSERVED
ADVERSE EFFECT LEVEL) - 6.7 MG/KG

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL,
PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE
NOT BEEN THOROUGHLY INVESTIGATED.

STOMACH - IRREGULARITIES - BASED ON HUMAN
EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	
TOXICITY TO FISH	SEMI-STATIC TEST LC50 - ONCORHYNCHUS MYKISS (RAINBOW TROUT) - 15.3 MG/L - 96 H REMARKS: (ECHA)
TOXICITY TO DAPHNIA AND OTHER AQUATIC INVERTEBRATES	STATIC TEST LC50 - CERIODAPHNIA DUBIA (WATER FLEA) - 0.074 MG/L – 48 H REMARKS: (ECHA)
TOXICITY TO ALGAE	STATIC TEST EC50 - PSEUDOKIRCHNERIELLA SUBCAPITATA (GREEN ALGAE) - > 81.5 - 148 MG/L - 72 H (OECD TEST GUIDELINE 201)
TOXICITY TO DAPHNIA AND OTHER AQUATIC INVERTEBRATES (CHRONIC TOXICITY)	SEMI-STATIC TEST EC10 - CERIODAPHNIA DUBIA (WATER FLEA) - > 2.8 - 53.6 MG/L - 7 D (US-EPA)
PERSISTENCE AND DEGRADABILITY	THE METHODS FOR DETERMINING BIODEGRADABILITY ARE NOT APPLICABLE TO INORGANIC SUBSTANCES.
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT	WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH THE NATIONAL AND LOCAL REGULATIONS. LEAVE CHEMICALS IN ORIGINAL CONTAINERS. NO MIXING WITH OTHER WASTE. HANDLE UNCLEARED CONTAINERS LIKE THE PRODUCT ITSELF.
CONTAMINATED PACKAGING	DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: METAL POWDER, FLAMMABLE, N.O.S. (Nickel powder (1.0-1.5 micron))
UN NUMBER: 3089
CLASS: 4.1
PACKING GROUP: II
REPORTABLE QUANTITY (RQ):
POISON INHALATION HAZARD: NO

IMDG

PROPER SHIPPING NAME: METAL POWDER, FLAMMABLE, N.O.S. (Nickel powder (1.0-1.5 micron))
UN NUMBER: 3089
CLASS: 4.1
PACKING GROUP: II
EMS-NO: F-G, S-G
MARINE POLLUTANT : YES

IATA

PROPER SHIPPING NAME: METAL POWDER, FLAMMABLE, N.O.S. (Nickel powder (1.0-1.5 micron))
UN NUMBER: 3089
CLASS: 4.1
PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY COMPONENTS WITH A SECTION 302 EHS TPQ.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS FIRE HAZARD, ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

	CAS NO.	REVISION DATE
NICKEL POWDER (1.0-1.5 MICRON)	7440-02-0	02-16-1993

CALIFORNIA PROP. 65 COMPONENTS

WHICH IS/ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

	CAS NO.	REVISION DATE
NICKEL POWDER (1.0-1.5 MICRON)	7440-02-0	04-11-2017

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H317	MAY CAUSE AN ALLERGIC SKIN REACTION.
H351	SUSPECTED OF CAUSING CANCER
H372	CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE IF INHALED.
H412	HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

MSDS LEGEND

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION: 3.2

REVISION DATE: 08/06/2025