



SAFETY DATA SHEET

United States

Section 1. Identification

Product name

HisTrap™ FF crude, 1 ml, 5 x 1 ml

Catalogue Number

11000458



Other means of identification

Not available.

Product type

Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Laboratory chemicals
Liquid chromatography.
Scientific research and development
Consumer use

Supplier

Cytiva
Amersham Place
Little Chalfont
Buckinghamshire
HP7 9NA United Kingdom
+44 1494 508000

Cytiva USA
100 Results Way
Marlborough, MA 01752
1-800-526-3593

In case of emergency

INFOTRAC - 24 Hour number: 1-800-535-5053
Outside of the United States, call 24 Hour number: 001-352-323-3500 (Call Collect)

Section 2. Hazards identification

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

FLAMMABLE LIQUIDS - Category 3
SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 2

GHS label elements

Hazard pictograms



Signal word

Warning

Hazard statements

Flammable liquid and vapor.
May cause an allergic skin reaction.
Suspected of causing cancer.

Precautionary statements

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves: 1 - 4 hours (breakthrough time): butyl rubber, neoprene. Wear protective clothing: Recommended: lab coat. Wear eye or face protection: Recommended: safety glasses with side-shields. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.

Response

IF exposed or concerned: Get medical advice or attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs: Get medical advice or attention.



Storage	Store locked up.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	None known.
Hazards identified when used	No known significant effects or critical hazards.

Section 3. Composition/information on ingredients

Substance/mixture	Mixture
Other means of identification	Not available.

Ingredient name	Synonyms	%	Identifiers
ethanol	ethyl alcohol; ALCOHOL; Ethyl alcohol (Ethanol); EtOH; Grain alcohol; Cologne spirit; undenatured ethyl alcohol, of an alcoholic strength by volume of 80 % or more and containing up to 20 % activated carbon; aqueous solution, containing by weight - 25 % or more, but not more than 35 % of a copolymer of vinyl caprolactam, vinyl pyrrolidone, N, N-dimethylaminopropyl methacrylamide and 3-(methacryloylamino) propyllauryldimethylammonium chloride, - 10 % or more, but not more than 16 % of ethanol whether or not denatured with tert-butyl alcohol and/or denatonium benzoate; Blend, consisting of ethyl alcohol, ethyl acetate and aldehydes, higher alcohols and water; blend, consisting of ethyl alcohol, ethyl acetate and water; Denatured Alcohol	≥10 - ≤30	CAS: 64-17-5
nickel		≥0.1 - ≤1	CAS: 7440-02-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	No known significant effects or critical hazards.
Inhalation	No known significant effects or critical hazards.
Skin contact	May cause an allergic skin reaction.
Ingestion	No known significant effects or critical hazards.

Over-exposure signs/symptoms



Eye contact	No specific data.
Inhalation	No specific data.
Skin contact	Adverse symptoms may include the following: irritation redness
Ingestion	No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures**Extinguishing media**

Suitable extinguishing media	Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Section 7. Handling and storage**Precautions for safe handling**

Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling)
----------------------------	---



	equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store between the following temperatures: 4 to 30°C (39.2 to 86°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
ethanol	NIOSH REL (United States, 10/2020) TWA 10 hours: 1000 ppm. TWA 10 hours: 1900 mg/m³. CAL OSHA PEL (United States, 1/2025) TWA 8 hours: 1900 mg/m³. TWA 8 hours: 1000 ppm. OSHA PEL (United States, 5/2018) TWA 8 hours: 1000 ppm. TWA 8 hours: 1900 mg/m³. OSHA PEL 1989 (United States, 3/1989) TWA 8 hours: 1000 ppm. TWA 8 hours: 1900 mg/m³. ACGIH TLV (United States, 1/2024) A3. STEL 15 minutes: 1000 ppm.
nickel	NIOSH REL (United States, 10/2020) [nickel metal and other compounds] NIA. TWA 10 hours: 0.015 mg/m³ (as Ni). CAL OSHA PEL (United States, 1/2025) TWA 8 hours: 0.5 mg/m³ (as Ni). OSHA PEL (United States, 5/2018) [Nickel, metal and insoluble compounds] TWA 8 hours: 1 mg/m³ (as Ni). OSHA PEL 1989 (United States, 3/1989) [Nickel, metal and insoluble compounds (as Ni)] TWA 8 hours: 1 mg/m³ (as Ni). ACGIH TLV (United States, 1/2024) A5. TWA 8 hours: 1.5 mg/m³. Form: Inhalable fraction.

Biological exposure indices

Ingredient name	Exposure indices
nickel	ACGIH BEI (United States, 1/2024) [nickel and inorganic compounds] BEI: 30 µg/l, nickel [in urine after exposure to soluble compounds]. Sampling time: post-shift at end of workweek. BEI: 5 µg/l, nickel [in urine after exposure to elemental nickel and poorly soluble compounds]. Sampling time: post-shift at end of workweek.

Appropriate engineering controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields

Skin protection**Hand protection**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. 1 - 4 hours (breakthrough time): butyl rubber, neoprene

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Recommended: lab coat

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Personal protective equipment (Pictograms)

Section 9. Physical and chemical properties

Appearance**Physical state**

Liquid.

Color

Blue. Green.

Odor

Alcohol-like. [Slight]

Odor threshold

180 ppm

pH

5.5 to 8.5 [Conc. (% w/w): 100%]

Melting point/freezing point

Not available.

Boiling point or initial boiling point and boiling range

Not available.

Flash point

Closed cup: 38 to 43°C (100.4 to 109.4°F)

Burning time

Not applicable.

Burning rate

Not applicable.

Evaporation rate

Not available.

Flammability

Not available.

Lower and upper explosive (flammable) limits

Not available.

Vapor pressure

Not available.

Vapor Pressure at 20°C**Vapor pressure at 50°C**

	Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
	ethanol	42.94865	5.7				
	water	17.5	2.3				
	Agarose	0	0				
Relative vapor density	Not available.						
Relative density	Not available.						
Solubility(ies)							
	Media	Result					
	cold water	Easily soluble					
	hot water	Easily soluble					
Solubility in water	Not available.						



Miscible with water Yes.**Partition coefficient: n-octanol/
water** Not applicable.**Auto-ignition temperature** Not available.

Ingredient name	°C	°F	Method
ethanol	455	851	DIN 51794

Decomposition temperature Not available.**SADT** Not available.**Viscosity** Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C (104°F)): Not available.**Flow time (ISO 2431)** Not available.**Particle characteristics****Median particle size** Not applicable.**Section 10. Stability and reactivity****Reactivity** No specific test data related to reactivity available for this product or its ingredients.**Chemical stability** The product is stable.**Possibility of hazardous
reactions** Under normal conditions of storage and use, hazardous reactions will not occur.**Conditions to avoid** Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.**Incompatible materials** Reactive or incompatible with the following materials:
oxidizing materials**Hazardous decomposition
products** Under normal conditions of storage and use, hazardous decomposition products should not be produced.**Section 11. Toxicological information****Information on toxicological effects****Acute toxicity****Product/ingredient name**
ethanol**Result****Rat - Oral - LD50**

7060 mg/kg

Toxic effects: Lung, Thorax, or Respiration - Other changes**Rat - Inhalation - LC50 Vapor**124700 mg/m³ [4 hours]**Conclusion/Summary
[Product]** Not available.**Skin corrosion/irritation****Product/ingredient name**
nickel**Result****Human - Skin - Severe irritant**Duration of treatment/exposure: 48 hoursAmount/concentration applied: 5 pph**Conclusion/Summary
[Product]** Not available.**Serious eye damage/eye irritation**

Not available.

**Conclusion/Summary
[Product]** Not available.**Respiratory corrosion/irritation**

Not available.

**Conclusion/Summary
[Product]** Not available.**Respiratory or skin sensitization**

Not available.



Skin

**Conclusion/Summary
[Product]** Not available.

Respiratory

**Conclusion/Summary
[Product]** Not available.

Germ cell mutagenicity

Not available.

**Conclusion/Summary
[Product]** Not available.

Carcinogenicity

Not available.

**Conclusion/Summary
[Product]** Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
nickel	-	2B	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

Not available.

**Conclusion/Summary
[Product]** Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
nickel	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Aspiration hazard

Not available.

**Information on the likely routes
of exposure** Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact	No known significant effects or critical hazards.
Inhalation	No known significant effects or critical hazards.
Skin contact	May cause an allergic skin reaction.
Ingestion	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	No specific data.
Inhalation	No specific data.
Skin contact	Adverse symptoms may include the following: irritation redness
Ingestion	No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure**Short term exposure**

Potential immediate effects	Not available.
Potential delayed effects	Not available.
Long term exposure	
Potential immediate effects	Not available.
Potential delayed effects	Not available.
Potential chronic health effects	
Not available.	
Conclusion/Summary [Product]	Not available.
General	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	No known significant effects or critical hazards.
Reproductive toxicity	No known significant effects or critical hazards.
Numerical measures of toxicity	
Acute toxicity estimates	
Product/ingredient name	Oral (mg/kg)Dermal (mg/kg)Inhalation (gases) (ppm)Inhalation (vapors) (mg/l)Inhalation (dusts and mists) (mg/l)
ethanol	7000N/AN/AN/A124.7N/A
Other information	
Adverse symptoms include the following: kidney abnormalities liver abnormalities	
Adverse symptoms may include the following: central nervous system depression	

Section 12. Ecological information

Toxicity

Product/ingredient name	Result
ethanol	Acute - LC50 - Marine water Fish - Bleak - <i>Alburnus alburnus</i> Size: 8 to 10 cm 11 g/l [96 hours] Effect: Mortality Chronic - NOEC - Marine water Algae - Green algae - <i>Ulva pertusa</i> 4.995 mg/l [96 hours] Effect: Reproduction Acute - EC50 - Fresh water Crustaceans - Ostracod - <i>Cypris subglobosa</i> 1074 mg/l [48 hours] Effect: Intoxication Chronic - NOEC - Fresh water Daphnia - Water flea - <i>Daphnia magna</i> - Neonate Age: <24 hours 100 µl/l [21 days] Effect: Mortality Acute - EC50 - Marine water Algae - Green algae - <i>Ulva pertusa</i> Size: 9.4 mm 3306 mg/l [96 hours] Effect: Reproduction Acute - EC50 - Fresh water Aquatic plants - Duckweed - <i>Lemna minor</i> 450 µg/l [4 days] Effect: Growth Chronic - NOEC - Marine water Algae - Dinoflagellate - <i>Glenodinium halli</i> 100 mg/l [72 hours] Effect: Population Acute - LC50 - Fresh water US EPA, OECD Crustaceans - Water flea - <i>Ceriodaphnia dubia</i> - Juvenile (Fledgling, Hatchling, Weanling) Age: 2 to 8 hours 34.6 µg/l [48 hours] Effect: Mortality
nickel	



		Chronic - EC10 OECD Daphnia - Water flea - <i>Daphnia magna</i> - Neonate <u>Age</u> : <24 hours 6.9 µg/l [21 days] <u>Effect</u> : Reproduction Acute - LC50 - Fresh water Fish - Indian catfish - <i>Heteropneustes fossilis</i> 47.5 ng/l [96 hours] <u>Effect</u> : Mortality	
Conclusion/Summary [Product]	Not available.		
<u>Persistence and degradability</u>			
Product/ingredient name ethanol	Result Aerobic 100% [20 days] - Readily		
Product/ingredient name ethanol	Aquatic half-life -	Photolysis -	Biodegradability Readily
<u>Bioaccumulative potential</u>			
Product/ingredient name ethanol Nickel	LogP_{ow} -0.35 -	BCF 0.66 16	Potential Low Low
<u>Mobility in soil</u>			
Soil/Water partition coefficient	Not available.		
Other adverse effects	No known significant effects or critical hazards.		

Section 13. Disposal considerations

Disposal methods	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste stream	Code: D001 Classification: Ignitability

Section 14. Transport information

Product is not regulated as dangerous goods for transport.

Section 15. Regulatory information

U.S. Federal regulations	TSCA 8(a) CDR Exempt/Partial exemption : Not determined Clean Water Act (CWA) 307 : Nickel
---------------------------------	---

TSCA 12(b) - Chemical export notification

Not applicable.

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	Listed
Clean Air Act Section 602 Class I Substances	Not listed
Clean Air Act Section 602 Class II Substances	Not listed
DEA List I Chemicals (Precursor Chemicals)	Not listed
DEA List II Chemicals (Essential Chemicals)	Not listed

SARA 302/304

Composition/information on ingredients



No products were found.

SARA 304 RQ Not applicable.

SARA 311/312

Classification
FLAMMABLE LIQUIDS - Category 3
SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 2

Composition/information on ingredients

Name	%	Classification
ethanol	14 - 19	FLAMMABLE LIQUIDS - Category 2
nickel	0.12	SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Nickel	7440-02-0	0.12
Supplier notification	Nickel	7440-02-0	0.12

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts	The following components are listed: ETHYL ALCOHOL
New York	None of the components are listed.
New Jersey	The following components are listed: ETHYL ALCOHOL; NICKEL
Pennsylvania	The following components are listed: ETHANOL

California Prop. 65

WARNING: This product can expose you to Nickel, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Nickel	-	-

International regulations**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)


Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

United States	Not determined.
Canada inventory	All components are listed or exempted.

Section 16. Other information**National Fire Protection Association (U.S.A.)****Procedure used to derive the classification**

Classification

Justification



FLAMMABLE LIQUIDS - Category 3	On basis of test data
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method

History

Date of printing	8/1/2025
Date of issue/Date of revision	8/1/2025
Date of previous issue	9/29/2023
Version	9
	sds_author@cytiva.com

Key to abbreviations

- ATE = Acute Toxicity Estimate
 - BCF = Bioconcentration Factor
 - GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 - IATA = International Air Transport Association
 - IBC = Intermediate Bulk Container
 - IMDG = International Maritime Dangerous Goods
 - LogPow = logarithm of the octanol/water partition coefficient
 - MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 - N/A = Not available
 - UN = United Nations
- Not available.

References

▢ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

