Stannous Chloride, 10% w/v

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 05/07/2015 Revision date: 08/26/2021 Supersedes: 04/25/2018 Version: 1.2

SECTION 1: Identification

1.1. Identification

Product form : Mixtures

Product name : Stannous Chloride, 10% w/v

Product code : LC25180

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only.

Recommended use : Laboratory chemicals

Restrictions on use : Not for food, drug or household use

1.3. Supplier

LabChem, Inc.

1010 Jackson's Pointe Ct.

Zelienople, PA 16063 - USA

T 412-826-5230 - F 724-473-0647

info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or +1-703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 1 H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS US) : P260 - Do not breathe mist, vapors, spray.
P264 - Wash exposed skin thoroughly after handling.
P280 - Wear protective gloves, eye protection, protective clothing, face protection.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a poison center or doctor/physician.
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to comply with local, state and federal regulations.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Water	(CAS-No.) 7732-18-5	81.5	Not classified
Stannous Chloride, Dihydrate	(CAS-No.) 10025-69-1	10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402
Hydrochloric Acid, 37% w/w	(CAS-No.) 7647-01-0	8.5	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : Possible inflammation of the respiratory tract.

Symptoms/effects after skin contact : Caustic burns/corrosion of the skin.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Nausea. Vomiting. Irritation of the gastric/intestinal mucosa. Diarrhoea.

Chronic symptoms : Affection/discolouration of the teeth.

4.3. Immediate medical attention and special treatment, if necessary

Obtain medical assistance.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Not flammable.

Explosion hazard : Not applicable.

Reactivity in case of fire : Thermal decomposition generates : Corrosive vapors.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Try to stop release. Dike and contain spill.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses. Protective clothing. Face-shield.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mist, vapors, spray.

Hygiene measures : Wash exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : incompatible materials. Keep container closed when not in use.

Incompatible products : metals. cyanides. Strong bases.

Incompatible materials : Direct sunlight.

Packaging materials : Do not store in corrodable metal.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Stannous Chloride, 10% w/v	
No additional information available	

Hydrochloric Acid, 37% w/w (7647-01-0)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH Ceiling (mg/m³)	2.98 mg/m³
ACGIH Ceiling (ppm)	2 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (Ceiling)	7 mg/m³
OSHA PEL C [ppm]	5 ppm
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	50 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (Ceiling)	7 mg/m³
NIOSH REL C [ppm]	5 ppm

Water (7732-18-5)
No additional information available

Stannous Chloride, Dihydrate (10025-69-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	2 mg/m³ (Inhalable fraction)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	2 mg/m³
USA - IDLH - Occupational Exposure Limits	
IDLH	100 mg/m³ as Sn
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	2 mg/m³

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Chemical resistant apron. Gloves. Safety glasses. Protective clothing.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Respiratory protection not required in normal conditions

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Color	:	Colorless
Odor	:	Odorless
Odor threshold	:	No data available
pH	:	≤ 0.5
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Flammability (solid, gas)	:	Non flammable.
Vapor pressure	:	No data available
Relative vapor density at 20 °C	:	No data available
Relative density	:	No data available

Density	:	1.1 – 1.2
Molecular mass	:	36.46 g/mol
Solubility	:	Soluble in water. Soluble in acids.
Log Pow	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
No data availableViscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
Explosion limits	:	No data available
Explosive properties	:	Not applicable.
Oxidizing properties	:	None.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts violently with (some) bases: release of heat.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

metals. cyanides. Strong bases.

10.6. Hazardous decomposition products

Hydrogen chloride. Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

Hydrochloric Acid, 37% w/w (7647-01-0)	
LD50 oral rat	700 mg/kg
LD50 dermal rabbit	5010 mg/kg
ATE US (oral)	700 mg/kg body weight
ATE US (dermal)	5010 mg/kg body weight

Water (7732-18-5)	
LD50 oral rat	≥ 90000 mg/kg
ATE US (oral)	90000 mg/kg body weight

Stannous Chloride, Dihydrate (10025-69-1)	
LD50 oral rat	700 mg/kg (RTECS)
LC50 Inhalation - Rat	2 mg/l (OECD 436: Acute inhalation toxicity-acute toxic class method, 4 h, Rat, Male / female, Experimental value, Inhalation (dust))
ATE US (oral)	700 mg/kg body weight
ATE US (vapors)	2 mg/l/4h
ATE US (dust, mist)	2 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns.

pH: ≤ 0.5

Serious eye damage/irritation	:	Causes serious eye damage. pH: ≤ 0.5
Respiratory or skin sensitization	:	Not classified
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Not classified
STOT-single exposure	:	Not classified

Hydrochloric Acid, 37% w/w (7647-01-0)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure	:	Not classified
Aspiration hazard	:	Not classified
Viscosity, kinematic	:	No data available
Likely routes of exposure	:	Skin and eye contact.
Potential Adverse human health effects and symptoms	:	Based on available data, the classification criteria are not met.
Symptoms/effects	:	Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	:	Possible inflammation of the respiratory tract.
Symptoms/effects after skin contact	:	Caustic burns/corrosion of the skin.
Symptoms/effects after eye contact	:	Causes serious eye damage.
Symptoms/effects after ingestion	:	Nausea. Vomiting. Irritation of the gastric/intestinal mucosa. Diarrhoea.
Chronic symptoms	:	Affection/discolouration of the teeth.

SECTION 12: Ecological information

12.1. Toxicity

Hydrochloric Acid, 37% w/w (7647-01-0)	
LC50 fish 1	282 mg/l (96 h, Gambusia affinis, Pure substance)
EC50 Daphnia 1	< 56 mg/l (72 h, Daphnia magna, Pure substance)

Stannous Chloride, Dihydrate (10025-69-1)	
EC50 Daphnia 1	22 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Anhydrous form)

12.2. Persistence and degradability

Stannous Chloride, 10% w/v	
Persistence and degradability	Not established.

Hydrochloric Acid, 37% w/w (7647-01-0)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

Water (7732-18-5)	
Persistence and degradability	Not established.

Stannous Chloride, Dihydrate (10025-69-1)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

Stannous Chloride, 10% w/v	
Bioaccumulative potential	Not established.

Hydrochloric Acid, 37% w/w (7647-01-0)	
Log Pow	0.25 (QSAR)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Water (7732-18-5)	
Bioaccumulative potential	Not established.

Stannous Chloride, Dihydrate (10025-69-1)	
BCF other aquatic organisms 1	0.76 – 6.41 (30 day(s), Mollusca, Static system, Salt water, Experimental value, Anhydrous form)
Log Pow	-2.1506 (Anhydrous form, Calculated, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

Hydrochloric Acid, 37% w/w (7647-01-0)	
Ecology - soil	No (test)data on mobility of the component(s) available. May be harmful to plant growth, blooming and fruit formation.

Stannous Chloride, Dihydrate (10025-69-1)	
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1789 Hydrochloric acid, 8, II

UN-No.(DOT) : UN1789

Proper Shipping Name (DOT) : Hydrochloric acid

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger

Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102)	:	386 - Notwithstanding the provisions of §177.834(l) of this subchapter, cargo heaters may be used when weather conditions are such that the freezing of a wetted explosive material is likely. Shipments must be made by private, leased or contract carrier vehicles under exclusive use of the offeror. Cargo heaters must be reverse refrigeration (heat pump) units. Shipments made in accordance with this Special provision are excepted from the requirements of §173.60(b)(4) of this subchapter. A3 - For combination packaging, if glass inner packaging (including ampoules) are used, they must be packed with absorbent material in tightly closed metal receptacles before packing in outer packaging. A6 - For combination packaging, if plastic inner packaging are used, they must be packed in tightly closed metal receptacles before packing in outer packaging. B3 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks and DOT 57 portable tanks are not authorized. B15 - Packaging must be protected with non-metallic linings impervious to the lading or have a suitable corrosion allowance. B133 - Hydrochloric acid concentration not exceeding 38%, in Packing Group II, is authorized to be packaged in UN31H1 or UN31HH1 intermediate bulk containers when loaded in accordance with the requirements of §173.35(h) of this subchapter. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. N41 - Metal construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material. T8 - 4 178.274(d)(2) Normal..... Prohibited TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	30 L
DOT Vessel Stowage Location	:	C - The material must be stowed ‘‘on deck only’’ on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	:	157
Other information	:	No supplementary information available.

Transport by sea (IMDG)

UN-No. (IMDG)	:	1789
Proper Shipping Name (IMDG)	:	HYDROCHLORIC ACID
Class (IMDG)	:	8 - Corrosive substances
Packing group (IMDG)	:	II - substances presenting medium danger
Limited quantities (IMDG)	:	1 L

Air transport (IATA/ICAO)

UN-No. (IATA)	:	1789
Proper Shipping Name (IATA)	:	Hydrochloric acid
Class (IATA)	:	8 - Corrosives
Packing group (IATA)	:	II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Stannous Chloride, 10% w/v	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Hydrochloric Acid, 37% w/w	CAS-No. 7647-01-0	8.5%
Water	CAS-No. 7732-18-5	81.5%
Stannous Chloride, Dihydrate	CAS-No. 10025-69-1	10%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Hydrochloric Acid, 37% w/w	CAS-No. 7647-01-0	8.5%

Hydrochloric Acid, 37% w/w (7647-01-0)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb
SARA Section 311/312 Hazard Classes	Health hazard - Acute toxicity (any route of exposure) Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation Health hazard - Specific target organ toxicity (single or repeated exposure)

Stannous Chloride, Dihydrate (10025-69-1)	
SARA Section 311/312 Hazard Classes	Health hazard - Acute toxicity (any route of exposure) Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation

15.2. International regulations

CANADA

Water (7732-18-5)
Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


Revision date : 08/26/2021

Other information : None.

Full text of H- and EUH-statements: see section 16:

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H332	Harmful if inhaled
H335	May cause respiratory irritation
H402	Harmful to aquatic life

NFPA health hazard	:	3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard	:	0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.
NFPA reactivity	:	1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



Hazard Rating

Health	:	3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	:	0 Minimal Hazard - Materials that will not burn
Physical	:	1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.
Personal protection	:	D D - Face shield and eye protection, Gloves, Synthetic apron

SDS US LabChem

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.