

Undercounter and Countertop Refrigerators

Lab and Pharmacy Refrigerators



UCR Series

Temperature range 2°C to 8°C / 35°F to 46°F

Door type Solid Door Glass Door

Internal capacity 75L 2.64 cu.ft. 130L 4.6 cu.ft.

Specifications

Model	UCR001	UCR001G	UCR101	UCR101G
Capacity	75L / 2.64 cu.ft.	75L / 2.64 cu.ft.	130L / 4.6 cu.ft.	130L / 4.6 cu.ft.
Door	Single solid, lockable (keyed)	Single glass, lockable (keyed)	Single solid, lockable (keyed)	Single glass, lockable (keyed)
Temperature range	2°C to 8°C / 35°F to 46°F			
Digital type	Microprocessor, digital			
Alarms	Hi / Low temperature, door ajar power failure, low battery sensor failure, USB failure			
Porthole	1" diameter			
Storage	2 adjustable shelves, 1 basket			
Insulation	US EPA and SNAP approved			
Exterior	Steel			
Refrigerant	R600a			
Compressor	Hermetic compressor			
Air circulation	Forced air			
Defrost	Automatic			
Exterior construction	Painted white			
Casters	2 rear, with leveling feet			
Internal dimensions (WxDxH)	17.5" x 17.5" x 21.75" 44 x 44 x 54 cm		21.5" x 20" x 23.25" 55 x 51 x 59 cm	
External dimensions (WxDxH)	21.25" x 22" x 30" 54 x 56 x 76 cm		25.75" x 24.75" x 32" 65 x 63 x 81 cm	
Weight	150 lbs.		165 lbs.	
Voltage	115V, 60 Hz, 1 phase			
Amperage line / running	15amd dedicated / 2.28A			
NEMA configuration	NEMA 5-15, comes with plug			
Optional accessories	Chart recorder, cold safety gloves, extra shelves			



75L
UCR001

130L
UCR101



75L
UCR001G

130L
UCR101G