



Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

SECTION 1: Identification

1.1. Product Identifier

Trade Name or Designation Potassium Hydroxide, 0.500 Normal (N/2) in Ethanol

Product Number R6265400

Other Identifying Product Numbers R6265400-120A, R6265400-1A

1.2. Recommended Use and Restrictions on Use

General Laboratory Reagent

1.3. Details of the Supplier of the Safety Data Sheet

Company Ricca Chemical Company

Address 412 West Fork Drive

Arlington, TX 76012 USA

Telephone 888-467-4222

1.4. Emergency Telephone Number (24 hours)

CHEMTREC (USA) 800-424-9300

CHEMTREC (International) 1+ 703-527-3887

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

SECTION 2: Hazard(s) Identification

2.1. Classification of the Substance or Mixture

Hazard Class	Category	Hazard Statements	Precautionary Statements
Flammable Liquids	Category 2	H225	P210,P233,P240,P241,P242,P243, P280,P303+P361+P353,P370+P378, P403+P235,P501
Skin Corrosion / Irritation	Category 2	H315	P264,P280,P302+P352,P321, P332+P313,P362+P364
Serious Eye Damage / Eye Irritation	Category 1	H318	P280,P305+P351+P338,P310

2.2. GHS Label Elements

Pictograms:



Signal Word: Danger

Hazard Statements:

NOTE: Hazard statements may be combined on labels to improve clarity and readability.

Hazard Number	Hazard Statement
H225	Highly flammable liquid and vapor
H315	Causes skin irritation
H318	Causes serious eye damage

Precautionary Statements:

NOTE: Precautionary statements may be combined or consolidated on labels to improve clarity and readability.

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

Prevention

Precautionary Number	Precautionary Statement
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharge.
P264	Wash hands, arms, and face thoroughly after handling.
P280	Wear protective gloves and eye protection.

Response

Precautionary Number	Precautionary Statement
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center or doctor.
P332+P313	If skin irritation occurs: Get medical advice or attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use dry chemical, foam, or carbon dioxide to extinguish.

Storage

Precautionary Number	Precautionary Statement
P403+P235	Store in a well-ventilated place. Keep cool.

Disposal

Precautionary Number	Precautionary Statement
P501	Dispose of contents/container to suitable waste stream in accordance with local, state, federal, and international regulations.

2.3. Hazards not Otherwise Classified

No other hazards identified.

2.4. Ingredients of Unknown Acute Toxicity

95.6 percent of this mixture consists of ingredient(s) of unknown acute dermal toxicity. 3.6 percent of this mixture consists of ingredient(s) of unknown acute inhalation toxicity.

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

SECTION 3: Composition / Information on Ingredients

3.1. Components of Mixture

Chemical Name (IUPAC)	Common Name and Synonyms	CAS Number	Weight%
ethanol	Ethyl Alcohol	64-17-5	91.95
water	Water	7732-18-5	4.41
potassium hydroxide	Potassium Hydroxide; caustic potash	1310-58-3	3.61
ethane-1,2-diamine	Ethylenediamine; 1,2-diaminoethane	107-15-3	< 0.1

SECTION 4: First-Aid Measures

4.1. Description of Necessary Measures

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. May cause irritation with burning and stinging with possible damage to the cornea and conjunctiva.

Ingestion: Do NOT induce vomiting.

Inhalation: Not expected to require first aid. If necessary, remove to fresh air.

Skin Contact: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Results in drying and cracking which can lead to secondary infections and dermatitis. Dermal absorption causes many of the symptoms of inhalation.

4.2. Most Important Symptoms and Effects, Acute and Delayed

Causes skin irritation Flammable liquid. Mildly corrosive. Primarily toxic by ingestion. Cannot be made non-poisonous. If ingested, give large quantity of water and induce vomiting. Call a physician. Contact may cause dryness and cracking of the skin. May cause irritation to the eyes. Wash areas of contact with water. May cause irritation of the respiratory system. EYE CONTACT: May cause irritation with burning and stinging with possible damage to the cornea and conjunctiva. SKIN CONTACT: Results in drying and cracking which can lead to secondary infections and dermatitis. Dermal absorption causes many of the symptoms of inhalation.

4.3. Immediate Medical Attention or Special Treatment Needed

Immediately call a poison center or doctor. Irrigate immediately with large quantity of water for at least 15 minutes. Call a physician if irritation develops. Remove to fresh air. Give artificial respiration if necessary. If breathing is difficult, give oxygen. Wash areas of contact with soap and water for at least 15 minutes. Call a physician if irritation develops. Dilute immediately with water or milk. Induce vomiting. Call a physician.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing Media

In case of fire: Use dry chemical, foam, or carbon dioxide to extinguish. Use any means suitable for extinguishing surrounding fire. Use water spray to blanket fire, cool fire exposed containers, and to flush non-ignited spills or vapors away from fire.

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

5.2. Specific Hazards Arising from the Substance or Mixture in a Fire

Highly flammable liquid and vapor Moderate explosion hazard and dangerous fire hazard when exposed to heat, sparks and open flames. Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Sensitive to static discharge.

5.3. Special Protective Equipment and Precautions for Firefighters

Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Ground and bond container and receiving equipment. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharge. Wear protective gloves and eye protection.

6.2. Cleanup and Containment Methods and Materials

Remove all sources of ignition. Contain spill. Do not flush to sewer. Absorb with suitable inert material (vermiculite, dry sand, etc) and place in a chemical waste container for proper disposal in an approved waste disposal facility. Ventilate area of spill. Have extinguishing agent available in case of fire. Use non-sparking tools and equipment. Dispose of in accordance with local regulations.

SECTION 7: Handling and Storage

7.1. Precautions for Safe Handling and Storage Conditions

Store in a well-ventilated place. Keep cool. As with all chemicals, wash hands thoroughly after handling. Avoid contact with eyes and skin. Protect from freezing and physical damage. Store in secure, flammable storage area away from all sources of ignition. Empty containers may be hazardous since they retain product residues.

SECTION 8: Exposure Controls / Personal Protection

8.1. Exposure Limits

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

U.S. OSHA - Permissible Exposure Limits (PEL) - Time Weighted Averages (TWA)

Chemical Name	CAS Number	Exposure Limit
Ethylenediamine	107-15-3	10 ppm TWA; 25 mg/m ³ TWA
Ethyl Alcohol	64-17-5	1000 ppm TWA; 1900 mg/m ³ TWA

U.S. OSHA - Permissible Exposure Limits (PEL) - Ceiling Limits

No limits found.

U.S. OSHA - Permissible Exposure Limits (PEL) - Short Term Exposure Limits (STEL)

No limits found.

U.S. OSHA - Specifically Regulated Chemicals

No limits found.

ACGIH - Threshold Limit Values - Ceilings (TLV-C)

Chemical Name	CAS Number	Exposure Limit
Potassium Hydroxide	1310-58-3	2 mg/m ³ Ceiling

ACGIH - Threshold Limit Values - Short Term Exposure Limits (TLV-STEL)

Chemical Name	CAS Number	Exposure Limit
Ethyl Alcohol	64-17-5	1000 ppm STEL

ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)

Chemical Name	CAS Number	Exposure Limit
Ethylenediamine	107-15-3	10 ppm TWA

8.2. Engineering Controls

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limit.

8.3. Individual Protective Measures and Personal Protective Equipment

Respiratory Protection: Normal room ventilation is adequate. If the exposure limit is exceeded, a full facepiece respirator with organic vapor cartridge may be worn.

Skin Protection: Chemical resistant gloves.

Eye Protection: Safety glasses or goggles.

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

SECTION 9: Physical and Chemical Properties

9.1. Basic Physical and Chemical Properties

Physical State:	Liquid
Color:	Colorless
Odor:	Data not available.
Odor Threshold:	Data not available.
Melting/Freezing Point:	Data not available.
Boiling Point/Range:	Data not available.
Flammability:	Data not available.
Flammability/Explosive Limits:	Data not available.
Flash Point:	13 °C (calculated)
Auto-Ignition Temperature:	Data not available.
Decomposition Temperature:	Data not available.
pH:	> 13
Kinematic Viscosity:	Data not available.
Solubility:	miscible
Vapor Pressure:	Data not available.
Evaporation Rate:	Data not available.
Relative Density:	0.82
Relative Vapor Density:	Data not available.
Particle Characteristics:	Data not available.
Partition Coefficient n-octanol/water, log	Data not available.

NOTE: Flash point was calculated according to the method of Gmehling and Rasmussen (Ind. Eng. Chem. Fundament, 21, 186, (1982)), as allowed by GHS Rev 7, section 2.6.4.2.3.

SECTION 10: Stability and Reactivity

10.1. Reactivity and Chemical Stability

Stable under normal conditions of use and storage.

10.2. Possibility of Hazardous Reactions

Data not available.

10.3. Conditions to Avoid and Incompatible Materials

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Oxidizers, platinum, Sodium, Potassium Dioxide, Bromine Pentafluoride, Acetyl Bromide, Acetyl Chloride, heat, sparks, open flame.

10.4. Hazardous Decomposition Products

Will not occur.

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

SECTION 11: Toxicological Information

11.1. Information on Toxicological Effects

Acute Toxicity - Oral Exposure:

Not acutely toxic.

Chemical Name	CAS Number	Toxicity
Ethylenediamine	107-15-3	Oral LD50 Rat 1160 mg/kg (Source: Canada_WHMIS)
Potassium Hydroxide	1310-58-3	Oral LD50 Rat 205 mg/kg (Source: Canada_HSA)
Ethyl Alcohol	64-17-5	Oral LD50 Rat 7060 mg/kg (Source: NLM_CIP)

Acute Toxicity - Dermal Exposure:

Not acutely toxic.

Chemical Name	CAS Number	Toxicity
Ethylenediamine	107-15-3	Dermal LD50 Rabbit 560 mg/kg (Source: JAPAN_GHS)

Acute Toxicity - Inhalation Exposure:

Inhalation acute toxicity estimate (ATE, vapor): 49000.0000 mg/L, 4 h(calculated)

Chemical Name	CAS Number	Toxicity
Ethylenediamine	107-15-3	Inhalation LC50 Rat 14.7 mg/L 4 h (vapor, Source: ECHA_API)
Ethyl Alcohol	64-17-5	Inhalation LC50 Rat 116.9 mg/L 4 h (males, vapor, Source: ECHA_API); Inhalation LC50 Rat 133.8 mg/L 4 h (females, vapor, Source: ECHA_API)

11.2 Carcinogenicity:

International Agency for Research on Cancer (IARC)

Chemical Name	CAS Number	Classification
No data found.		

National Toxicology Program (NTP)

Chemical Name	CAS Number	Classification
Ethyl Alcohol	64-17-5	Male Rat - Not Tested; Female Rat - Not Tested; Male Mice - Inadequate Experiment; Female Mice - Inadequate Experiment (TR-510)

U.S. OSHA specifically regulated carcinogens

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

Chemical Name	CAS Number	Classification
No data found.		

11.3 Additional Toxicology Information:

Causes skin irritation. Causes serious eye damage.

SECTION 12: Ecological Information

12.1. Ecotoxicity

Chemical Name	CAS Number	Species	Exposure	Toxicity
Ethyl Alcohol	64-17-5	Earthworm	Acute	LC50 48 h Eisenia foetida 0.1 - 1 mg/cm2 [filter paper] (IUCLID)
Ethylenediamine	107-15-3	Freshwater Algae	Acute	EC50 72 h Pseudokirchneriella subcapitata 645 mg/L (IUCLID); EC50 96 h Pseudokirchneriella subcapitata 151 mg/L (IUCLID)
Ethylenediamine	107-15-3	Freshwater Fish	Acute	LC50 96 h Pimephales promelas 98.6 - 131.6 mg/L [static] (EPA); LC50 96 h Pimephales promelas 191 - 254 mg/L [flow-through] (EPA); LC50 96 h Pimephales promelas 115.7 mg/L [semi-static] (IUCLID); LC50 96 h Poecilia reticulata 180 - 560 mg/L [semi-static] (EPA)
Ethyl Alcohol	64-17-5	Freshwater Fish	Acute	LC50 96 h Oncorhynchus mykiss 12.0 - 16.0 mL/L [static] (EPA); LC50 96 h Pimephales promelas >100 mg/L [static] (EPA); LC50 96 h Pimephales promelas 13400 - 15100 mg/L [flow-through] (EPA)
Ethylenediamine	107-15-3	Water Flea	Acute	EC50 48 h Daphnia magna 17 mg/L (IUCLID)
Ethyl Alcohol	64-17-5	Water Flea	Acute	LC50 48 h Daphnia magna 9268 - 14221 mg/L (IUCLID); EC50 48 h Daphnia magna 2 mg/L [Static] (EPA)

12.2. Persistence and Degradability

Data not available.

12.3. Bioaccumulative Potential

Data not available.

12.4. Mobility in soil

Data not available.

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

12.5. Other Adverse Ecological Effects

Data not available.

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

Data not available.

SECTION 14: Transportation Information

14.1 Transportation by Land - Department of Transportation (DOT, United States of America)

Sizes: 1 L, 120 mL

UN Number: UN2924

Proper Shipping Name: Flammable Liquid, Corrosive, n.o.s. (Ethanol, Potassium Hydroxide)

Hazard Class: 3 (8)

Packing Group: II

Hazard Label(s):



14.2 Transportation by Air - International Air Transport Association (IATA)

Sizes: 1 L, 120 mL

UN Number: UN2924

Proper Shipping Name: Flammable Liquid, Corrosive, n.o.s. (Ethanol, Potassium Hydroxide)

Hazard Class: 3 (8)

Packing Group: II

Hazard Label(s):





Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

14.3 Transportation of Dangerous Goods (TDG, Canada)

Sizes: 1 L, 120 mL

UN Number: UN2924

Proper Shipping Name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)

Hazard Class: 3 (8)

Packing Group: II

Hazard Label(s):



SECTION 15: Regulatory Information

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

15.01. Occupational Safety and Health Administration (OSHA) Hazards

Chemical Name	CAS Number	Regulatory Information
No data found.		

15.02. Superfund Amendments and Reauthorization Act (SARA) 302 Extremely Hazardous Substances

Chemical Name	CAS Number	RQ	TPQ
Ethylenediamine	107-15-3	10000 lb TPQ	5000 lb EPCRA RQ

15.03. Superfund Amendments and Reauthorization Act (SARA) 311/312 Hazardous Chemicals

Chemical Name	CAS Number	Regulatory Information
Ethylenediamine	107-15-3	5000 lb final RQ; 2270 kg final RQ
Potassium Hydroxide	1310-58-3	1000 lb final RQ; 454 kg final RQ

15.04. Superfund Amendments and Reauthorization Act (SARA) 313 Toxics Release Inventory (TRI)

Chemical Name	CAS Number	List
No data found.		

15.05. Massachusetts Right-to-Know Substance List

Chemical Name	CAS Number	Regulatory Information
Ethylenediamine	107-15-3	Extraordinarily hazardous
Potassium Hydroxide	1310-58-3	Present
Ethyl Alcohol	64-17-5	Teratogen

15.06. Pennsylvania Right-to-Know Hazardous Substances

Chemical Name	CAS Number	Regulatory Information
Ethylenediamine	107-15-3	Environmental hazard
Potassium Hydroxide	1310-58-3	Environmental hazard
Ethyl Alcohol	64-17-5	Present

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

15.07. New Jersey Worker and Community Right-to-Know Components

Chemical Name	CAS Number	Regulatory Information
Ethylenediamine	107-15-3	sn 0875
Potassium Hydroxide	1310-58-3	sn 1571
Ethyl Alcohol	64-17-5	sn 0844

15.08. California Proposition 65

Chemical Name	CAS Number	Regulatory Information
Ethyl Alcohol	64-17-5	"carcinogen, 7/1/1988 (when associated with alcohol abuse); carcinogen, 4/29/2011" As Alcoholic beverages [RR-01961-4]
Ethyl Alcohol	64-17-5	"developmental toxicity, 10/1/1987 (listed under Ethyl alcohol in alcoholic beverages)" As Alcoholic beverages [RR-01961-4]

15.09. Canada Domestic Substances List / Non-Domestic Substances List (DSL/NDSL)

Chemical Name	CAS Number	List	Status
Ethylenediamine	107-15-3	DSL	Present
Potassium Hydroxide	1310-58-3	DSL	Present
Ethyl Alcohol	64-17-5	DSL	Present
Ethyl Alcohol	64-17-5	NDSL	"Present" As Alcohols, C1-3 [68475-56-9]
Water	7732-18-5	DSL	Present

15.10. United States of America Toxic Substances Control Act (TSCA) List

Chemical Name	CAS Number	Status
Ethylenediamine	107-15-3	Present (ACTIVE)
Potassium Hydroxide	1310-58-3	Present (ACTIVE)
Ethyl Alcohol	64-17-5	Present (ACTIVE)
Water	7732-18-5	Present [XU] (ACTIVE)

15.11. European Inventory of Existing Commercial Chemical Substances (EINECS), European List of Notified Chemical Substances (ELINCS), and No Longer Polymers (NLP)

Chemical Name	CAS Number	List	Number
Ethylenediamine	107-15-3	EINECS	203-468-6
Potassium Hydroxide	1310-58-3	EINECS	215-181-3
Ethyl Alcohol	64-17-5	EINECS	200-578-6
Water	7732-18-5	EINECS	231-791-2

Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

15.12. China - Inventory of Existing chemical Substances (IECSC)

Chemical Name	CAS Number	Status
Ethylenediamine	107-15-3	Present [07146]
Potassium Hydroxide	1310-58-3	Present [27680]
Ethyl Alcohol	64-17-5	Present [38125]
Water	7732-18-5	Present [32224]

15.13. Korea - Existing Chemicals Inventory (KECI/KECL)

Chemical Name	CAS Number	List	Status
Ethylenediamine	107-15-3	Annex 1	Present [KE-13141]
Potassium Hydroxide	1310-58-3	Annex 1	Present [KE-29139]
Ethyl Alcohol	64-17-5	Annex 1	Present [KE-13217]
Water	7732-18-5	Annex 1	Present [KE-35400]


15.14. Japan - Existing and New Chemical Substances Inventory (ENCS)

Chemical Name	CAS Number	MITI No.
Ethylenediamine	107-15-3	(2)-150
Potassium Hydroxide	1310-58-3	(1)-369
Ethyl Alcohol	64-17-5	(2)-202
Water	7732-18-5	- (listed on Japanese Pharmacopoeia 8th Edition)

SECTION 16: Other Information

16.1 National Fire Protection Associate (NFPA) Rating

Health: 2
Flammability: 3
Reactivity: 0
Special Hazard:





Safety Data Sheet

Classified According to OSHA Hazard Communication Standard (HCS 2024)

16.2 Document Revision

Last Revision Date:

2026-05-07

DISCLAIMER

When handled properly by qualified personnel, the product described herein does not present a significant health or safety hazard. Alteration of its characteristics by concentration, evaporation, addition of other substances, or other means may present hazards not specifically addressed herein and which must be evaluated by the user. The information furnished herein is believed to be accurate and represents the best data currently available to us. No warranty, expressed or implied, is made and RICCA CHEMICAL COMPANY assumes no legal responsibility or liability whatsoever resulting from its use.